

PEEL & SEAL™

SELF-STICK ALUMINUM ROLL ROOFING

Peel & Seal™ is the original, self-stick roll roofing specifically designed for low slope residential and commercial applications. Composed of a patented formula (consisting of laminated aluminized foil, high-density polymer films and a thick layer of rubberized asphalt), Peel & Seal provides a long lasting, durable, maintenance-free roofing surface.

From dormers, residential sunroom additions, “open” porches, and mobile home roofs, to industrial and agricultural buildings where low slope roofs are common place, Peel & Seal is an excellent solution for these applications. The self-adhering, weatherproof, reflective surface not only forms a highly effective barrier to the elements, but also limits solar heating to help keep the temperature of building interiors significantly cooler.



Applying Peel & Seal is easy. No tar, torches, mops, glues, tapes, or fasteners are required a scissors



or knife and hand roller are the only tools needed. Following preparation of the surface, simply peel off the release paper, unroll Peel & Seal to the proper length.

Maintenance-free Peel & Seal will not crack or dry out after being applied, is available in a choice of finishes (aluminum, almond, white, and granite gray), and conveniently sized in 100 sq. ft. cartons in roll widths of 3”, 4”, 6”, 9”, 12”, 18” and 36”.

Peel & Seal is perfect for hundreds of uses ranging from full-roof applications to patching gutters and vent pipes. Fully pliable and providing a secure seal at edges, corners and over gaps, it is ideal for roof areas that are often difficult to waterproof, including locations where ducts, vents, chimneys, or air conditioning units either protrude through, or are roof mounted.

Peel & Seal: The original, maintenance-free, energy efficient, economical, self-sealing roll roofing you can count on for any low slope/low pitch application and **warranted by MFM for 10 full years!**



Typical Peel & Seal Properties:

Roll Width	36”, 18”, 12”, 6”, 4”
Roll Length	33.5’
Carton Coverage	100 sq ft
Carton Weight	32 lbs
Thickness	45 mils
Tear Strength	640 g
Elongation	380%
Application Temperature	55° - 110° F
Service Temperature	-25° - 150° F




“As an ENERGY STAR® Roof Products Partner, MFM Building Products Corp. has determined that aluminum surface PEEL & SEAL™ meets the ENERGY STAR® guidelines for energy efficiency.”



Made in USA


Roofing: Peel & Seal



Aluminum



Beige



Gray



White

NOTE: WE CARRY ALUMINUM FINISH. Other colors are available by special order only. *Please call for pricing and availability.*

A - Alum Peel & Seal™ 4” x 33’	H-1003-79
White Peel & Seal™ 4” x 33’	H-1003-791
Alum Peel & Seal™ 6” x 33’	H-1003-8
Alum Peel & Seal™ 12” x 33.5’	H-1003-81
Alum Peel & Seal™ 18” x 33.5’	H-1003-82
Alum Peel & Seal™ 36” x 33.5’	H-1003-83